NOTE:
Actual results achieved may vary from predicted values due to normal deviation in luminaire installation, electrical supply, equipment tolerances, obstructions including poles, brackets and mounting arms, reflectances etc.

This design is for general guidance only & its use is subject to conditions (available on request).

Based On
Lumen Output at 20000 Hours,
Lumen Output per Lamp Manufacturers Data,
Spot Lamp Replacement,
Normal Environment,
Annual Cleaning,
Ground is Level.

Calculation Summary

Description	Avg	Max	Min	Min/Avg	Min/Max	Units	PtSpcLr	PtSpcTb	# Pts
Pitch	118.47	164	74	0.62	0.45	Lux	3.5	3.5	98

Luminaire Schedule

Symbol	Qty	Label	Lumens/Lamp	LLF	Description	Filename
	8	SP3	35985	0.900	Sportslite 300w LED 5K, Asymmetric 55D	5SP1300GA-A55.IES

VeeLite

Project:
Training Level Pitch

Client:

Project No:	Drawing No:	Drawn By:
18-01-45	18-01-45-09	PK
Date: 09/03/2018	Scale: As shown	REV NO: A

18-01-45-09.AGI

Luminaire Location Summary

LumNo	Label	X	Y	Z	Orient	Tilt
1	SP3	11.5	25.6	12	240	5
2	SP3	12.25	25.6	12	290	5
3	SP3	37.75	25.6	12	250	5
4	SP3	38.5	25.6	12	300	5
5	SP3	11.5	-0.6	12	120	5
6	SP3	12.25	-0.6	12	70	5
7	SP3	37.75	-0.6	12	110	5
8	SP3	38.5	-0.6	12	60	5

Total Quantity: 8